

TOTT 2

Floodlight



Product features

- Easy installation and toolless wiring
- Fixing bracket adjustable up to 355°
- Special design of mounting bracket allows more spacious for power drill
- Stainless 304 screws equipped
- DC input compatible (DC180-260V)
- Attachable PIR module available



Applications

- Gate area
- Signage
- Billboard
- Warehouse
- Industrial area
- Sport facility
- Garden

TOTT 2

Product datasheet

Floodlight

Product information

	Item No.	Description	Power (W)	Lumen (lm)	Light efficacy (lm/W)	CCT (K)	Beam angle (°)	Dimmable
	710655	TOTT2 9,5W 3000K	9.5	980	103	3000	110	No
	710656	TOTT2 24W 3000K	24	2470	103	3000	110	No
	710657	TOTT2 45W 3000K	45	4650	103	3000	110	No
	710658	TOTT2 85W 3000K	85	9860	116	3000	110	No
	710677	TOTT2 85W 4000K	85	10600	125	4000	110	No

Electrical data

Max. number of luminaires per miniature circuit breaker

Item No.	THD	Inrush current I _{peak} (A)	Inrush current time (μs)	B10	B16	C10	C16	Surge protection (V)
710655	0.2	17.8	130	12	19	19	32	2000
710656	0.2	21.8	130	10	15	16	26	2000
710657	0.2	35.6	150	6	9	10	16	2000
710658	0.2	38.4	240	3	5	5	8	2000
710677	0.2	38.4	240	3	5	5	8	2000

TOTT 2

Floodlight

General specifications

Electrical data	
Nominal voltage	220-240V
Frequency	50/60Hz
Power factor (PF)	>0,9
Protection class	Class II
Photometric data	
CRI	RA80
UGR	N/A
Colour consistency (SDCM)	6
Flicker percentage	≤30% @100Hz
Photobiological safety group	RG1
Mounting & application	
Mounting method	Surface mounted
Loop-through	No
Driver	Integrated
IP rating	IP65
IK rating	IK08
Glow wire test	650°C
Lifetime	50000h L70B50 at 25°C, 30000h L80B10
Switching cycles	100000
Operating temperature	-30 to 50°C
Warranty	5 years
Materials	
Material	PC, PC
Certificates	
Standards	CE

TOTT 2

Floodlight

Product dimensions & weight

Item No.	L (mm)	W (mm)	H (mm)	Net weight (kg)
710655	105	132	60	0,18
710656	197	217	84	0,39
710657	197	260	84	0,55
710658	297	338	89	1,45
710677	297	338	89	1,45

Master box information

Item No.	Units / master box	L (mm)	W (mm)	H (mm)	Gross weight (kg)
710655	10	322	240	306	6.1
710656	5	370	228	424	6.06
710657	4	370	228	512	8
710658	1	362	342	336	8.9
710677	2	362	342	336	8.9



TOTT 2

Floodlight

Product datasheet

Accessories

Item No.	710830										
	Sensor kit										
710656											
710657											
710658											
710677											