

A60

Bulb



Applications

- Hotel
- Restaurant
- Retail
- Patio
- Residence
- Institution (museum/church/etc.)



15000h L70



Product information

Energy efficiency class	Item No.	Cap	Power (W)	Equivalent power (W)	Useful lumen (lm)	Light efficacy (lm/W)	CCT (K)	Beam angle (°)	Dimmable
	143316	E27	8.6	60	806	94	2700	180	No
	143372	E27	8.6	60	806	94	4000	180	No
	710614	E27	9.6	75	1055	110	2700	240	No
	709886	E27	9	75	1055	117	4000	240	No

General specifications

Electrical data	
Nominal voltage	220-240V
Frequency	50/60Hz
Power factor (PF)	≥0,70
Input current	59mA
Surge protection	500V
Photometric data	
CRI	RA80
Colour consistency (SDCM)	6
Flicker percentage	≤8% @100Hz
Photobiological safety group	RG0
Mounting & application	
Mounting method	In retrofit luminaire
IP rating	IP20
Lifetime	15000h L70B50 at 25°C
Switching cycles	50000
Operating temperature	-30 to 45°C
Warranty	2 years
Materials	
Material	PC, Aluminium cap
Certificates	
Standards	CE, ERP

A60

Bulb

Product dimensions & weight

Item No.	Cut-out Ø (mm)	Ø (mm)	H (mm)	Net weight (kg)
143316	N/A	59	106	0,026
143372	N/A	59	106	0,026
710614	N/A	60	109	0,025
709886	N/A	60	109	0,0278

Master box information

Item No.	Units / master box	L (mm)	W (mm)	H (mm)	Gross weight (kg)
143316	60	411	333	267	3.73
143372	60	385	321	247	3.26
710614	60	378	315	235	3.73
709886	60	378	315	235	3.297