

TEMPUS Surface downlight

Emergency lighting



Product features

- Non-maintained operation mode
- Super slim design
- Overcharge and over-discharge protection, over-temperature protection, short circuit protection
- Status indicator
- IP54 protection
- Open area optics

**EMERGENCY****CLASS II****50000h L70**

Applications

- Open area
- Escape route

TEMPUS Surface downlight

Product datasheet

Emergency lighting

Product information

	Item No.	Description	Power (W)	Lumen (lm)	Light efficacy (lm/W)	CCT (K)	Beam angle (°)	Dimmable
	710482	TEMPUS Surface M DL Open area	3.1	135	44	6000	140	No
	710483	TEMPUS Surface M DL Corridor	3.1	135	44	6000	150	No

Electrical data

Max. number of luminaires per miniature circuit breaker

Item No.	THD	Inrush current I _{peak} (A)	Inrush current time (μs)	B10	B16	C10	C16	Surge protection (V)
710482	N/A	10.6	200	20	31	32	53	500
710483	N/A	10.6	200	20	31	32	53	500

TEMPUS Surface downlight

Product datasheet

Emergency lighting

General specifications

Electrical data	
Nominal voltage	220-240V
Frequency	50/60Hz
Power factor (PF)	0.5
Protection class	Class II
Photometric data	
CRI	RA80
UGR	N/A
Colour consistency (SDCM)	6
Photobiological safety group	RG0
Mounting & application	
Mounting method	Surface mounted
Loop-through	No
Driver	Integrated
IP rating	IP54
IK rating	IK02
Glow wire test	850°C
Lifetime	50000h L70B50 at 25°C
Switching cycles	100000
Operating temperature	0 to 45°C
Warranty	3 years
Materials	
Material	PC
Certificates	
Standards	

TEMPUS Surface downlight

Product datasheet

Emergency lighting

Product dimensions & weight

Item No.	L (mm)	W (mm)	H (mm)	Net weight (kg)
710482	130	130	35	0,243
710483	130	130	35	0,243

Master box information

Item No.	Units / master box	L (mm)	W (mm)	H (mm)	Gross weight (kg)
710482	40	540	340	210	10.5
710483	40	540	340	210	10.5



TEMPUS Surface downlight

Product datasheet

Emergency lighting

Accessories

/											
---	--	--	--	--	--	--	--	--	--	--	--