

ROCCA

Waterproof



Product features

- Replacement for traditional waterproof batten
- Durable water and vandal resistant construction with IP65 and IK08 rating
- Easy installation and toolless wiring
- Durable stainless steel clips



SENSOR



EMERGENCY



IP65



IK08



CLASS I



40000h L70



Applications

- Parking garage
- Warehouse
- Industrial area
- Underground area
- Workshop

Product information

Item No.	Description	Power (W)	Lumen (lm)	Light efficacy (lm/W)	CCT (K)	Beam angle (°)	Dimmable
711345	ROCCA 20W L1270	20	2500	125	4000	110	No
711346	ROCCA 28W L1270	28	3600	129	4000	110	No
711438	ROCCA 30W L655	30	3600	120	4000	110	No
711439	ROCCA Emergency 34W L655	34	3600	106	4000	110	No
711440	ROCCA 40W L1265	40	4800	120	4000	110	No
712018	ROCCA Sensor 41W L1265	41	4800	117	4000	110	No
711441	ROCCA Emergency 44W L1265	44	4800	109	4000	110	No
711442	ROCCA 56W L1565	56	6800	121	4000	110	No
712019	ROCCA Sensor 57W L1565	57	6800	119	4000	110	No
711443	ROCCA Emergency 60W L1565	60	6800	113	4000	110	No
711344	ROCCA 70W L1865	70	9100	130	4000	110	No

Electrical data

Max. number of luminaires per miniature circuit breaker

Item No.	THD	Inrush current I _{peak} (A)	Inrush current time (μs)	B10	B16	C10	C16	Surge protection (V)
711345	0.16	30	58	19	30	31	50	500
711346	0.15	30	60	19	30	31	50	1000
711438	0.15	30	60	19	30	31	50	1000
711439	0.15	30	60	19	30	31	50	1000
711440	0.14	45	81	12	20	21	34	1000
712018	0.14	45	81	12	20	21	34	1000
711441	0.14	45	81	12	20	21	34	1000
711442	0.15	45	78	12	20	21	34	1000
712019	0.15	45	78	12	20	21	34	1000
711443	0.15	50	78	11	18	18	30	1000
711344	0.1	50	75	11	18	18	30	1000

General specifications

Electrical data	
Nominal voltage	220-240V
Frequency	50/60Hz
Power factor (PF)	>0,9
Protection class	Class I
Photometric data	
CRI	RA80
UGR	N/A
Colour consistency (SDCM)	6
Flicker percentage	≤3% @100Hz
Photobiological safety group	RG0
Mounting & application	
Mounting method	Surface mounted / Suspended
Loop-through	No
Driver	Integrated
IP rating	IP65
IK rating	IK08
Glow wire test	850°C
Lifetime	40000h L70B50 at 25°C
Switching cycles	100000
Operating temperature	-30 to 50°C
Warranty	3 years
Materials	
Material	ABS, Anti-UV PC
Certificates	
Standards	CE



Product dimensions & weight

Item No.	L (mm)	W (mm)	H (mm)	Net weight (kg)
711345	1270	76	83	1,08
711346	1270	76	83	1,288
711438	655	102	86	0,878
711439	655	102	86	1,148
711440	1265	102	86	1,55
712018	1265	102	86	1,65
711441	1265	102	86	1,82
711442	1565	102	86	1,83
712019	1565	102	86	1,9
711443	1565	102	86	2,1
711344	1865	148	86	2,85

Master box information

Item No.	Units / master box	L (mm)	W (mm)	H (mm)	Gross weight (kg)
711345	6	1298	255	260	12
711346	6	1598	255	260	14.1
711438	6	688	380	260	9.9
711439	6	688	380	260	12.6
711440	6	1298	260	260	16.7
712018	6	1298	260	260	17
711441	6	1298	260	260	19.4
711442	6	1598	260	260	13.6
712019	6	1598	260	260	14.2
711443	6	1598	260	260	10.22
711344	6	1886	293	324	25.7

ROCCA

Product datasheet

Waterproof

Accessories

/											
---	--	--	--	--	--	--	--	--	--	--	--