

RONDA

Bulkhead



Product features

- IP65 waterproof protection and IK08 rated vandal resistant
- Cost effective LED outdoor bulkhead solution
- Homogenous light output
- Loop-through function to further enhance ease of installation



Applications

- Parking garage
- Warehouse
- Industrial area
- Staircase
- Garden

RONDA

Product datasheet

Bulkhead

Product information

	Item No.	Description	Power (W)	Lumen (lm)	Light efficacy (lm/W)	CCT (K)	Beam angle (°)	Dimmable
	711461	RONDA 18W 3000K	18	1560	87	3000	120	No
	711412	RONDA 18W 4000K	18	1650	92	4000	120	No
	711435	RONDA 24W 3000K	24	2090	87	3000	120	No
	711413	RONDA 24W 4000K	24	2200	92	4000	120	No

Electrical data

Max. number of luminaires per miniature circuit breaker

Item No.	THD	Inrush current I _{peak} (A)	Inrush current time (μs)	B10	B16	C10	C16	Surge protection (V)
711461	0.34	7.88	22.4	71	113	117	192	500
711412	0.34	7.88	22.4	71	113	117	192	500
711435	0.33	7.96	21.6	70	112	116	190	500
711413	0.33	7.96	21.6	70	112	116	190	500

RONDA

Bulkhead

General specifications

Electrical data	
Nominal voltage	220-240V
Frequency	50/60Hz
Power factor (PF)	>0,9
Protection class	Class II
Photometric data	
CRI	RA80
UGR	N/A
Colour consistency (SDCM)	6
Flicker percentage	≤3% @100Hz
Photobiological safety group	RG0
Mounting & application	
Mounting method	Surface mounted
Loop-through	Yes
Driver	Integrated
IP rating	IP65
IK rating	IK08
Glow wire test	650°C
Lifetime	30000h L70B50 at 25°C
Switching cycles	100000
Operating temperature	-30 to 50°C
Warranty	3 years
Materials	
Material	PC, PC
Certificates	
Standards	CE

RONDA

Bulkhead

Product dimensions & weight

Item No.	Cut-out Ø (mm)	Ø (mm)	H (mm)	Net weight (kg)
711461	N/A	300	100	0,75
711412	N/A	300	100	0,75
711435	N/A	300	100	0,75
711413	N/A	300	100	0,75

Master box information

Item No.	Units / master box	L (mm)	W (mm)	H (mm)	Gross weight (kg)
711461	5	320	320	540	5.1
711412	5	320	320	540	5.1
711435	5	320	320	540	5.1
711413	5	320	320	540	5.1



Accessories

/											
---	--	--	--	--	--	--	--	--	--	--	--