

FRANCO

Bulkhead



Product features

- IP66 waterproof protection and IK10 rated vandal resistant
- Corrosion free tough polycarbonate enclosure & UV resistant
- 3-step multipower and dual CCT 3000/4000K
- Theft-proof screws
- High operating temperature allows use in outdoor environments under extreme weather
- Microwave motion sensor kit available with master-slave function of maximum 250W
- Emergency kit available with 300lm output energy backup lasting for 3 hours



DUAL CCT



IK10



CLASS II



50000h L70



Applications

- Parking garage
- Warehouse
- Industrial area
- Staircase
- Garden

Product information

	Item No.	Description	Power (W)	Lumen (lm)	Light efficacy (lm/W)	CCT (K)	Beam angle (°)	Dimmable
	710551	FRANCO White ring	10/15/22	930/1400/1860 1000/1500/2000	93/93/85 100/100/91	3000 4000	110	No
	710552	FRANCO Black ring	10/15/22	930/1400/1860 1000/1500/2000	93/93/85 100/100/91	3000 4000	110	No
	710553	FRANCO White half ring	10/15/22	641/956/1271 683/1029/1365	64/64/58 68/68/62	3000 4000	110	No
	710554	FRANCO Black half ring	10/15/22	610/910/1210 650/980/1300	61/61/55 65/65/59	3000 4000	110	No

Electrical data

Max. number of luminaires per miniature circuit breaker

Item No.	THD	Inrush current I _{peak} (A)	Inrush current time (μs)	B10	B16	C10	C16	Surge protection (V)
710551	<30%	25.4	200	8	13	14	22	500
710552	<30%	25.4	200	8	13	14	22	500
710553	<30%	25.4	200	8	13	14	22	500
710554	<30%	25.4	200	8	13	14	22	500

FRANCO

Bulkhead

General specifications

Electrical data	
Nominal voltage	220-240V
Frequency	50/60Hz
Power factor (PF)	>0,9
Protection class	Class II
Photometric data	
CRI	RA80
UGR	N/A
Colour consistency (SDCM)	6
Flicker percentage	≤3% @100Hz
Photobiological safety group	RG0
Mounting & application	
Mounting method	Surface mounted
Loop-through	Yes
Driver	Integrated
IP rating	IP66
IK rating	IK10
Glow wire test	850°C
Lifetime	50000h L70B50 at 25°C
Switching cycles	100000
Operating temperature	-30 to 50°C
Warranty	5 years
Materials	
Material	PC, Anti-UV PC, Aluminium ring
Certificates	
Standards	CE

Product dimensions & weight

Item No.	Cut-out Ø (mm)	Ø (mm)	H (mm)	Net weight (kg)
710551	N/A	309	88	1,28
710552	N/A	309	88	1,28
710553	N/A	309	88	1,497
710554	N/A	309	88	1,497

Master box information

Item No.	Units / master box	L (mm)	W (mm)	H (mm)	Gross weight (kg)
710551	6	655	301	349	9.84
710552	6	655	301	349	9.84
710553	6	655	301	349	7.128
710554	6	655	301	349	7.122



Bulkhead

Accessories

Item No.	710286/ 200030	710354/ 710267									
	Sensor kit	Emergency kit									
710551											
710552											
710553											
710554											