

MILENA DALI

Downlight



Product features

- Modular downlight with DALI2.0 and dual CCT 3000/4000K
- IP54 rated for damp location such as bathroom and kitchen
- Toolless terminal block and loop-through function to further enhance ease of installation
- High cut-off angle for better glare control
- Long lifetime of 50.000h L80B10 @ Ta 25°C



DUAL CCT



CLASS I



50000h L80



Applications

- Office
- Corridor
- Hotel
- Bathroom
- Kitchen
- Restaurant
- Retail

MILENA DALI

Product datasheet

Downlight

Product information

	Item No.	Description	Power (W)	Lumen (lm)	Light efficacy (lm/W)	CCT (K)	Beam angle (°)	Dimmable
	711000	MILENA DALI Ref 27W Ø172mm	27	2500 2700	93 100	3000 4000	90	DALI dim
	711001	MILENA DALI Ref 27W Ø225mm	27	2500 2700	93 100	3000 4000	90	DALI dim

Electrical data

Max. number of luminaires per miniature circuit breaker

Item No.	THD	Inrush current I _{peak} (A)	Inrush current time (μs)	B10	B16	C10	C16	Surge protection (V)
711000	<10%	11	50	33	52	54	88	1000
711001	<10%	11	50	33	52	54	88	1000

MILENA DALI

Downlight

General specifications

Electrical data	
Nominal voltage	220-240V
Frequency	50/60Hz
Power factor (PF)	>0,9
Protection class	Class I
Photometric data	
CRI	RA80
UGR	N/A
Colour consistency (SDCM)	4
Flicker percentage	≤3% @100Hz
Photobiological safety group	RG1
Mounting & application	
Mounting method	Recessed
Loop-through	Yes
Driver	External
IP rating	IP54
IK rating	N/A
Glow wire test	850°C
Lifetime	50000h L80B10 at 25°C
Switching cycles	100000
Operating temperature	-30 to 40°C
Warranty	5 years
Materials	
Material	PC + Aluminium, PC
Certificates	
Standards	CE

MILENA DALI

Downlight

Product dimensions & weight

Item No.	Cut-out Ø (mm)	Ø (mm)	H (mm)	Net weight (kg)
711000	150	172	87	0,76
711001	200	225	97	0,85

Master box information

Item No.	Units / master box	L (mm)	W (mm)	H (mm)	Gross weight (kg)
711000	12	406	335	450	10.2
711001	12	712	242	500	12.1



MILENA DALI

Product datasheet

Downlight

Accessories

/