

TEMPUS Slim bulkhead

Emergency lighting



Product features

- Maintained / non-maintained operation mode
- IP65 protection from water and dust
- Durable, corrosion resistant polycarbonate housing
- Status indicator
- All direction exit sign stickers included
- Light in weight, easy installation

**EMERGENCY****CLASS II**

Applications

- Corridor
- Escape route
- Office
- School
- Retail
- Open area

TEMPUS Slim bulkhead

Product datasheet

Emergency lighting

Product information

	Item No.	Description	Power (W)	Lumen (lm)	Light efficacy (lm/W)	CCT (K)	Beam angle (°)	Dimmable
	710474	TEMPUS Slim BH	4	140	35	6500	120	No
	711052	TEMPUS Slim BH Self-test	4	140	35	6500	120	No

Electrical data

Max. number of luminaires per miniature circuit breaker

Item No.	THD	Inrush current I _{peak} (A)	Inrush current time (μs)	B10	B16	C10	C16	Surge protection (V)
710474	N/A	N/A	N/A	20	28	25	40	500
711052	N/A	N/A	N/A	20	28	25	40	500

TEMPUS Slim bulkhead

Product datasheet

Emergency lighting

General specifications

Electrical data	
Nominal voltage	220-240V
Frequency	50/60Hz
Power factor (PF)	0.4
Protection class	Class II
Photometric data	
CRI	RA70
UGR	N/A
Colour consistency (SDCM)	6
Photobiological safety group	RG0
Mounting & application	
Mounting method	Surface mounted
Loop-through	No
Driver	Integrated
IP rating	IP65
IK rating	IK03
Glow wire test	850°C
Lifetime	L70B50 at 25°C
Switching cycles	100000
Operating temperature	0 to 40°C
Warranty	3 years
Materials	
Material	PC
Certificates	
Standards	

TEMPUS Slim bulkhead

Product datasheet

Emergency lighting

Product dimensions & weight

Item No.	L (mm)	W (mm)	H (mm)	Net weight (kg)
710474	352	110	67	0,61
711052	352	110	67	0,61

Master box information

Item No.	Units / master box	L (mm)	W (mm)	H (mm)	Gross weight (kg)
710474	12	332	385	385	8.4
711052	12	332	385	385	8.4



TEMPUS Slim bulkhead

Product datasheet

Emergency lighting

Accessories

/											
---	--	--	--	--	--	--	--	--	--	--	--