

TONO 2

Batten



Product features

- High competitive value-for-money batten
- Efficacy up to 114lm/W
- Slim design
- Equipped with 40cm 52(RVV) 2x 0.75mm² power cable



CLASS II



50000h L70



Applications

- Corridor
- Staircase
- Under cabinet
- Warehouse
- Production facility

TONO 2

Product datasheet

Batten

Product information

	Item No.	Description	Power (W)	Lumen (lm)	Light efficacy (lm/W)	CCT (K)	Beam angle (°)	Dimmable
	710239	TONO2 29W 3000K L900	29	3050	105	3000	110	No
	709982	TONO2 29W 4000K L900	29	3300	114	4000	110	No
	709955	TONO2 38W 3000K L1200	38	4050	107	3000	110	No
	709956	TONO2 38W 4000K L1200	38	4350	114	4000	110	No

Electrical data

Max. number of luminaires per miniature circuit breaker

Item No.	THD	Inrush current I _{peak} (A)	Inrush current time (μs)	B10	B16	C10	C16	Surge protection (V)
710239	0.3	25.6	250	7	11	11	19	1000
709982	0.3	25.6	250	7	11	11	19	1000
709955	0.3	24.2	350	6	10	10	16	1000
709956	0.3	24.2	350	6	10	10	16	1000

TONO 2

Batten

General specifications

Electrical data	
Nominal voltage	220-240V
Frequency	50/60Hz
Power factor (PF)	>0,9
Protection class	Class II
Photometric data	
CRI	RA80
UGR	N/A
Colour consistency (SDCM)	6
Flicker percentage	≤3% @100Hz
Photobiological safety group	RG0
Mounting & application	
Mounting method	Surface mounted
Loop-through	No
Driver	Integrated
IP rating	IP20
IK rating	N/A
Glow wire test	850°C
Lifetime	50000h L70B50 at 25°C
Switching cycles	100000
Operating temperature	-30 to 40°C
Warranty	5 years
Materials	
Material	PC, PC
Certificates	
Standards	CE

TONO 2

Product datasheet

Batten

Product dimensions & weight

Item No.	L (mm)	W (mm)	H (mm)	Net weight (kg)
710239	900	75	24	0,31
709982	900	75	24	0,31
709955	1200	75	24	0,385
709956	1200	75	24	0,385

Master box information

Item No.	Units / master box	L (mm)	W (mm)	H (mm)	Gross weight (kg)
710239	20	995	320	181	9.2
709982	20	995	320	181	9.2
709955	10	1298	165	185	5.2
709956	10	1298	165	185	5.2



TONO 2

Product datasheet

Batten

Accessories

/											
---	--	--	--	--	--	--	--	--	--	--	--